

## **Dönges Tripod Item Number JDDS5**

for Floodlight-Mounting

### Technical Specifications:

Maximum height:	4,75 m
Folded length:	1,12 m
Load capacity:	25 kg
Weight:	ca. 15 kg

Scope of delivery: 4-level extensible tripod with pin according to DIN 14640 and anchoring set, consisting of 3 suspension ropes and 3 tent pegs.

### Installation:

1. Unclose legs lashing strap, open tripod legs entirely and situate the tripod. Please watch the stabilizers guide (A) to come out until the stop position.
2. Pull out tripod-stands under consideration of terrain roughness and fix the stands by help of the locking screws (B). **ATTENTION:** It is essential to always fix **ALL** wing screws!
3. Now pull out telescopic tubes successively to the desired length and fix the wing screws **TIGHT**.  
**ATTENTION:** loose-fitting wing screws will lead to collapsing telescopic tubes under load. **RISK OF INJURY!**
4. Secure the tripod by help of attached anchoring set; use the anchorage ring (C). **ATTENTION:** Tripod has to be secured always with anchoring ropes, as otherwise the tripod might topple over by unintended push, wind gust, etc. **RISK OF INJURY!**
5. **Essential for tripod dismantling:**  
For the pull in please save the telescopic tube with one hand first before loosening the wing screw. This shall avoid the telescopic tube to rush down undamped!

